

| L Number | Hits | Search Text | DB | Time stamp |
|----------|------|---|---------------------------|------------------|
| 1 | 7291 | ((Shock and absorb\$5).ti.) | USPAT; US-PGPUB; EPO; JPO | 2003/01/08 11:39 |
| 6 | 595 | ((shock and absorb\$5).ti.) and vehicle.clm. | USPAT; US-PGPUB; EPO; JPO | 2003/01/08 11:39 |
| 11 | 2 | ((Shock and absorb\$5).ti.) and vehicle.clm.) and (two-wheeled).clm. | USPAT; US-PGPUB; EPO; JPO | 2003/01/08 11:42 |
| 16 | 2111 | (73/146-146.8).CCLS. | USPAT; US-PGPUB; EPO; JPO | 2003/01/08 11:43 |
| 21 | 51 | ((73/146-146.8).CCLS.) and ((pressure) near3 (maintain\$4 hold\$4 constant keep\$4)).clm. | USPAT; US-PGPUB; EPO; JPO | 2003/01/08 11:45 |

| | U |  | Document ID | Issue Date | Pages | Title |
|---|--------------------------|---|---------------|------------|-------|---|
| 1 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 6252498 B1 | 20010626 | 15 | Tire pressure detecting system for a vehicle |
| 2 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 6119514 A | 20000919 | 6 | Method and unit for detecting defects in the tread belt of a tire |
| 3 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5516379 A | 19960514 | 10 | CTI program pressure setting override |
| 4 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5313827 A | 19940524 | 11 | Method and apparatus for detecting ply defects in pneumatic tires |
| 5 | <input type="checkbox"/> | <input checked="" type="checkbox"/> | US 5228337 A | 19930720 | 12 | Tire pressure and temperature measurement system |